



PHONE: (909) 993-5700  
 EMAIL: sales@deluxebuildingproducts.com  
 LOCATION: 1350 E. Lexington Ave., Pomona, CA 91766



[www.DeluxeBuildingProducts.com](http://www.DeluxeBuildingProducts.com)

## Deluxe Building Products CRC Channel

### Geometric Properties

Deluxe Building Products CRC channels are fabricated with 1-1/2" webs and 1/2" flange height with 1/2" flange. All Deluxe Building Products hat channels are produced from hot-dipped galvanized steel in G60 coating. G90 is available on request.

### Steel Thickness

Mil Thickness	Design Thickness inches (mm)	Min Thickness inches (mm)
54 (16ga)	0.0566 (1.44mm)	0.0538 (1.37mm)

- 1) Uncoated Steel Thickness is for carbon steel
- 2) Minimum Thickness represents 95% of the design thickness and is the minimum acceptable thickness delivered to the job site based on the Section A4.3 of the AISI S100-2007

### Color Code (Painted On Ends)

54 Mil: Green

### LEED Points and Recycled Content

By using Deluxe Building Products your project can contribute to earning LEED points for:

- 1) LEED MR 2.1 and 2.2: Construction Waste Management: Up to 2 points.
- 2) LEED MR 4.1 and 4.2 Recycled Content: Up to 2 points.
- 3) LEED MR 5.1 and 5.2: Regional Materials

### Deluxe Building Products Cold-Formed Steel Framing Products Contain 30% To 35% Recycled Steel.

These products are produced from steel consisting of the following contents:

- 1) Total Recycled Content: 32.9%
- 2) Post-Consumer Content: 25.6%
- 3) Pre-Consumer Content: 6.8%

